

Dry-etching of indium and tin oxides

Publication number: TW387928B

Publication date: 2000-04-21

Inventor: CHEN JIE (CN); WONG YUEN-KUI (US)

Applicant: APPLIED KOMATSU TECHNOLOGY INC (JP)

Classification:

- international: **H01L21/302; H01L21/3213; H01L21/02; (IPC1-7):**
C09K13/00

- European: **H01L21/3213C4B**

Application number: TW19980109622 19980617

Priority number(s): US19970881950 19970625


Also published as:

WO9859381 (A1)
EP0990270 (A1)
US6036876 (A1)
EP0990270 (A0)

[Report a data error here](#)

Abstract of TW387928B

An etch method includes providing a material layer consisting essentially of a group member selected from the group consisting of an indium oxide (InO), a tin oxide (SnO), a mixture of indium and tin oxides, a compound of indium and of tin and of oxygen having the general formulation $\text{In}_x\text{Sn}_y\text{O}_z$ where z is substantially greater than zero but less than 100% and where the sum $x+y$ fills the remainder of the 100%, and a mixture of the preceding ones of the group members. A reactive gas including a halogen-containing compound and an oxygen-containing compound is supplied to a vicinity of the material layer. Also, an electric field is supplied to react the supplied reactive gas with the material layer so as to form volatile byproducts of reactive gas and the material layer.



Data supplied from the **esp@cenet** database - Worldwide